

24 Colors | 4 Sizes | 1 Finish

MEDLEY TERRAZZO PORCELAIN

NEMO
TILE + STONE



GREEN | POP GREEN



CLASSIC GREY | ROCK DARK GREY



PINK | ROCK PINK | CLASSIC PINK




ROCK WHITE | CLASSIC WHITE


V3 Variation | Matte Finish

MEDLEY


Medley reworks the classical style of Italian Terrazzo for contemporary taste. Comprised of a concrete, “Minimal,” together with 3 Venetian Terrazzo versions, “Classic,” “Rock,” and “Pop,” Medley evokes the idea of original Terrazzo compositions, while evolving it toward a new concept in which graphics and colors merge to a degree of creative freshness.




White



Pink



Green




Blue




Grey




Dark Grey




Classic White




Classic Pink




Classic Green




Classic Blue




Classic Grey




Classic Dark Grey




Pop White




Pop Pink




Pop Green



Pop Blue



Pop Grey



Pop Dark Grey



Rock White




Rock Pink




Rock Green



Rock Blue



Rock Grey




Rock Dark Grey


Size




24" x 48"



24" x 24"



12" x 24"



1" x 1"
on 12x12 Sheet

TRIM



BATTISCOPIA
2 3/4" x 23 5/8"



BATTISCOPIA
1 13/16" x 35 7/16"



GRADINO NATURALE
STAIR TREAD
12 15/16" x 47 1/4"



GRADONE NATURALE - STEP
12 15/16" x 47 1/4" x 1 1/4" x 1 1/4"




ANGOLARE NATURALE - STEP
12 15/16" x 47 1/4" x 1 1/4" x 1 1/4"



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/CG
UL 2818



放射性水平A类



Technical Information

PROPERTY	STANDARD	RESULT	
Water absorption	ISO 10545-3	Compliant	
	ASTM C373	Compliant	
		<u>9.5mm</u>	<u>20mm</u>
Modulus of rupture	ISO 10545--4	>45 N/mm^2	>45 N/mm^2
Breaking strength	ISO 10545-4	>2000 N	>12000 N
	ASTM C648	400 lbs	2500 lbs
Frost resistance	ISO 10545-12	Conforms	
	ASTM C1026	Unaffected	
Chemical resistance to high and low acid and basic concentrations	ISO 10545-13	A-LA-HA	
	ASTM C-650	Unaffected	
Stain resistance	ISO 10545-14	5	
		<u>Nat.</u>	<u>Tecnica 20mm</u>
Slip resistance	DIN EN 16165 Annex B	R10	R11
	DIN EN 16165 Annex A	B (A+B)	C (A+B+C)
	ANSI A326.3:2017 DCOF	Wet>0.50	Wet>0.65
	B.C.R.A. D.M. N. 236 14/6/89	>0.40	>0.40
	AS 4586-2012 Anexo A	P3	P4
	BS 7976-2: 2002 BSEN13036-4:2011 Pendulum testers	>36 Low slip potential	>36 Low slip potential
	UNE 41901:2017 EX DB SUA	-	3

Packing Information

SIZE	Thickness	PCS/Box	SF/Box	LBS/Box	Boxes/Pallet	SF/Pallet	LBS/Pallet
24x48	9.5mm	2	15.5	69.84	36	558	2513.27
24x24	9.5mm	3	11.63	52.38	40	465	2094.39
12x24	9.5mm	6	11.63	52.38	48	558	2513.27
36x36	9.5mm	2	17.44	78.57	24	418.5	1884.95
Mosaic	9.5mm	5	4.84	19.25	60	290.63	1155.22
24x48	20mm	1	7.75	73.02	36	279	2627.91

NEMO
TILE + STONE

MEDLEY
TERRAZZO LOOK PORCELAIN