

NEMO
TILE + STONE

STONE FICTION



STONE FICTION



STONE FICTION



STONE FICTION

COLORS



IVORY



BEIGE



SILVER



COFFEE



V3 MODERATE VARIATION

SIZES

Field Tile - Calibrated			Available in all colors	
Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
12 x 24	11-13/16 x 23-13/16	9.5	3/16	UPS
24 x 24	23-13/16 x 23-13/16	9.5	3/16	UPS/EXT
Note : Field tile is calibrated (non-rectified) with a minimum 3/16" grout joint				

STONE FICTION

MOSAICS



IVORY 2X2 MOSAIC



BEIGE 2X2 MOSAIC




SILVER 2X2 MOSAIC




COFFEE 2X2 MOSAIC

COORDINATING TRIMS



BULLNOSE

4"x24" - 7.2x60 cm



COVE BASE

6"x12" - 15x30 cm

SIZES

Mosaics

Nominal (in)	Actual Size (in)	Thickness (mm)	Grout Joint (in)	Finish
2 x 2 Mosaic*	11-15/16 x 11-15/16	9.5	3/16	UPS

* Mounted on 12 x 12 sheet with 3mm grout joints

Coordinating Trim

Available in all colors

Nominal (in)	Actual (in)	Thickness (mm)	Grout Joint (in)	Finish
6 x 12 Cove Base	5-7/8 x 11-3/4	9.5	3/16	UPS
4 x 24 Single Bullnose	3-13/16 x 23-13/16	9.5	3/16	UPS

STONE FICTION



STONE FICTION

Product Performance

Breaking Strength	>450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.42 - 0.52	ANSI A326.3
EXT	0.60 - 0.70	ANSI A326.3

Shade & Texture Index

Stone Fiction has a shade variation of V3.





NEMO
TILE + STONE

STONE FICTION